


GSG-D



Harte Stangengreifbacken


- Spitzverzahnung Zoll 1/16" x 90° oder 3/32" x 90°
- Spitzverzahnung geschliffen

Typ	Id.-Nr.	Spann- bereich Ø	B	H	N	Spitz- verzahnung	b für ISO 4762	kg / Satz
GSG-D 165 ¹	091343	15-40	30	40	14	1/16" x 90°	20 M10	1.06
GSG-D 200 ²	091344	15-50	35	45	17	1/16" x 90°	22 M12	1.50
GSG-D 250 ³	091345	20-70	45	50	21	1/16" x 90°	28 M16	2.69
GSG-D 400 ⁴	091346	40-100	55	60	25.5	3/32" x 90°	35 M20	7.78

* nur mit Einzelnutenstein
¹ Spannungsbereich gültig für Futter Ø 165
² Spannungsbereich gültig für Futter Ø 210
³ Spannungsbereich gültig für Futter Ø 260
⁴ Spannungsbereich gültig für Futter Ø 400

SMW-AUTOBLOK	Forkardt	Röhm	Schunk
HFKN-D 165 SP/STP 160 AN/AL/BH/HB-D 165 BHD-FC 165 PB/PB/RC-D 165 AP/NT-D 170 BB-D 175 HYND-S 180 HFKN-D 210 SP/STP 200/240 AN/AL/BH/BB-D 210 BHD-FC 210 CC 240Z HB/PB/PB/RC-D 210 AP/APL/NT-D 215 AP/APL/NT-D 260 HYND-S 210/226			TP 160
HFKN-D 260/315 SP/STP 280 SP/SP-L 350 AN/AL/BH/BB-D 250 AN/AL/BH/BB-D 315 BHD-FC 250/315 RC-D 250/305/400 CC 350Z HB/PB/PB/RC-D 250/315 AP/APL/NT-D 315 HYND-S 250/315/400	QLK/QLC 200 QLK/QLC-KS/LS 200 QLC-AG 200 NH/NHF 200 KL/KT/KTG/KTN/KS-PS 200 KS 200/250 KSF 200 KGH/KGHF/KTH 200 KG/KP 200 UVE 200	KFD/KFD-HF 200 KFH/KFH-F/KFH-G/KFH-NC 200 KFD-AF 200 KFD-HE 210 SPD/SPO 215 LVE 200	TH/THF/HSL 210 ROTA NCD 210 ROTA NC/ROTA NCF/ROTA NCO 210 ROTA NCK plus 210/250 ROTA TP 200 TP 200
HFKN-D 400/500 AP/AP-L/NT-D 400* BB-N 400/470/500/600 BB-N ES 400/470/500/600 BB-EXL(SC)2G 510/660 AN/AL/BB-D 400 BH-D 400/450/500/630/800 BHD-FC 400/500/630 IN/IL-D 500/630/800 HYDL-S 500/630/800	QLK/QLC 250/315 QLK/QLC-KS 315/400 QLK/QLC-LS 250/315 QLC-AG 250/315 KG/KT/KP/KTG/KTN/KTGF 250/315 KLNC/NH/NHF 250/315 KS 315/400 KSPS 250/300 KSH/KSHF 250/315/400 HF315 UVE315	KFD/KFD-HF 250/315 KFH/KFH-F/KFH-G/KFH-NC 250/315 KFD-AF 250/315 KFD-HE 254/315 KFL 315/400 SPD/SPO 300 LVE 250/305/315	TH/THF/HSL 250/315 ROTA NC/ROTA NCD 250/315 ROTA NCF 250/315 ROTA NCO 260/315 ROTA NCK plus 315 ROTA TP 250/315 TP 250/315
	QLK/QLC 400 NH/NHF 400/500/630 KT/KTGF 400/500/630 KS 500/630 KG/KL/KP/KLNC 400/500 KSHF 630 KSH 500 KSL 630 KSPS 400 UVE 400/500/630/800	KFD 400/500/630/800 KFD-HF 400/500/630 KFD-HS 400/500 KFD-HE 400 KFH/KFH-F/KFH-G/KFH-NC 400/500 KFL 500/600 KFD-HE 400 LVE 400/500/630/800/1000	TH/THF 400/500 HSL 400 HSG 400/500 ROTA NC/ROTA NCD 400/500 ROTA NCF/ROTA NCO 400/500

GFB-D



Harte Aufsatzbacken
für GF-80


- Spitzverzahnung Zoll 1/16" x 90°
- Spitzverzahnung geschliffen

Typ	Id.-Nr.	Spann- bereich Ø	B	H	N	Spitz- verzahnung	b für ISO 4762	kg / Satz
GFB-D 1	016348	5-25	25	39	10	1/16" x 90°	M8	0.64
GFB-D 2	016349	25-45	30	39	10	1/16" x 90°	M8	0.62
GFB-D 3	016350	45-65	30	39	10	1/16" x 90°	M8	0.53
GFB-D 4	016351	65-80	30	39	10	1/16" x 90°	M8	0.47
GFB-D 5	016352	80-100	30	39	10	1/16" x 90°	M8	0.51

SMW-AUTOBLOK	Forkardt	Röhm	Schunk
GF 80		GF 80	
GF 80		GF 80	
GF 80		GF 80	
GF 80		GF 80	
GF 80		GF 80	



SMW-AUTOBLOK
188, 190



SMW-AUTOBLOK
65