


Weiche Aufsatzbacken für Zwei-, Drei- und Vierbacken-Kraftspannfutter

- American Standard Kreuzversatz
- Werkstoff: C45

Typ	Id.-Nr.	B	H ₂	L	N	D	E	I	ISO 4762	kg / Stück	SMW-AUTOBLOK
WAKA 165*	12041660	30	32	80	7.94	30	38	12.68	M10	0.47	RAN 160 AN-C 165 HB-C 165 PB-C 165 PBI-C 165 AP-C 170 NT-C 170
WAKA 210*	12042060	35	37	100	7.94	35	44.4	12.68	M12	0.81	RAN 200 AN-C 210 HB-C 210 PB-C 210 PBI-C 210 AP-C 215 APL-C 215 NT-C 215
WAKA 250*	12042560	45	42	120	12.7	42	54	19.03	M16	1.40	AN-C 250 HB-C 250 PB-C 250 PBI-C 250 RAN 250 AP-C 260 APL-C 260 NT-C 260
WAKA 315*	12043060	50	47	140	12.7	50	63.5	19.03	M16	2.14	AN-C 315 HB-C 315 PB-C 315 PBI-C 315 RAN 315 AP-C 315 APL-C 315 NT-C 315
WAKA 400	12044050	60	55	165	12.7	60	76.2	19.03	M20	3.53	AN-C 400 AP-C 400 APL-C 315 NT-C 400 RAN 400
WAKA 500	12045050	75	70	165	12.7	60	76.2	19.03	M20	5.83	IL-C 500 IL-C 630 IL-C 800 IN-C 500 IN-C 630 IN-C 800

* Backen angeschrägt



SMW-AUTOBLOK
96, 188



SMW-AUTOBLOK
76