


Weiche Aufsatzbacken
für Backenschnellwechsel

- Kreuzversatz
- Werkstoff: 16MnCr5


Typ	Id.-Nr.	B	H ₁	H ₂	L	N	S	a	b	kg / Satz	SMW-AUTOBLOK
WAK 125-10	016633	20	30	27.5	55	14*	5*	25	20	0.61	
WAK 140-10	012490	20	40	36	69	8	18	26	32	0.89	KNCS-N 140
WAK 160-10	012491	20	40	36	85	8	18	42	32	1.15	HG-N 160 HG-F 160 KNCS-N 170 KNCS-2G 170
WAK 200-10	012492	22	46	42	105	10	20	50	40	1.91	HG-N 210 HG-F 210 KNCS-N 210 KNCS-N 225 KNCS-NB 210 KNCS-NB 225 KNCS-2G 210 KNCS-2G 225
WAK 200-10	012492-2**	22	46	42	105	10	20	50	40	1.30	KNCS-N 210
WAK 250-10	012493	30	55.5	50.5	125	12	20	70	40	3.72	HG-N 260 HG-N 315 HG-F 260 KNCS-N 260/275 KNCS-N 325/340 KNCS-NB 260 KNCS-NB 325 KNCS-NB 340 KNCS-2G 260 KNCS-2G 325
WAK 250-10	012493-2**	30	55.5	50	125	12	20	70	40	2.50	KNCS-N 260/325
WAK 400-10	012494	35	60	54	145	12	26	74	54	5.70	HG-N 400 HG-2G 400 HG-F 315 KNCS-N 400 KNCS-NB 400 KNCS-2G 400
WAK 500-10	012495	50	80	73	180	18	30	100	60	13.65	HG-N 500 HG-N 630 HG-2G 500 HG-2G 630 HG-F 400/ 500 KNCS-N 500 KNCS-N 630 KNCS-NB 500 KNCS-NB 630 KNCS-NB 800 KNCS-2G 500 KNCS-2G 630
WAK 630-10	080930	65	118	110	260	24	40	150	82	39.48	HG-F 630

* Nut
** Für 2-Backen-Futter
Andere Abmessungen sind ebenfalls lieferbar.


Forkardt	Samchully	Röhm	Schunk
F 125 F+125		Duro 125	
		Duro-NC 140 Duro-NC 168	
F 160 KTNC 160 KTNCV 160 KTNCV 175 FNC 175 F+160	QJC-206	Duro 160 Duro-NC 160 Duro-NCE 160 Duro-NC 175 Duro-NCE 175 Duro-NCES 175	ROTA-S plus 160 ROTA THW 165 ROTA THW plus 165/185 ROTA-G 160 • THW165 ROTA-S 160 ROTA NCW 185 ROTA-NCR 200
F 200 KTNC 200 KTNCV 200 FNC 200 F+200	QJC-208	Duro 200 Duro-NC 200 ROTA-NC 225 Duro-NCE 200 Duro-NCES 200	ROTA-S plus 200 ROTA THW 210 ROTA THW plus 215 ROTA-G 200 THW 210R/F ROTA NCW 225 ROTA-S 200 ROTA NCWF 210 ROTA THWB 210 ROTA THW vario 215
F 250 UNC 250/315 KTNC 250/265 KTNC 280/315 KTNCV 250 KTNCV 250 KTNCV 315 FNC 250 FNC 315 F+250	QJC-210 QJC-212	Duro 250 Duro-NC 250 Duro-NCE 250 Duro-NCE 315 Duro-NCES 250 Duro-NCES 315	ROTA-S plus 250 ROTA-THW 250/315 ROTA THW plus 260/315 ROTA-G 250/315 THW 250/265-R/F ROTA NCW 265/315 ROTA-S 250 ROTA-NCWF 250/315 ROTA THWB 265 THW 315-R
F 315 UNC 400 KTNC 360 KTNC 400 KTNCV 400 FNC 400 F+315	QJC-215	Duro 315 Duro-NC 315 Duro-NCE 400 Duro-NCES 400	ROTA-S plus 315 ROTA THW 400 THW 400-R/F ROTA-G 400 ROTA-S 315 ROTA THWB 315 THW315-F
F 400/500 L UNC 500 KTNC 500/630 KTNCV 500/630 FNC 500/630 F+400 F+500L	QJC-220	Duro 400/500 Duro-NC 400/500 Duro-NCE 500	ROTA-S plus 400/500 ROTA THW 500/630/800 ROTA-G 500 ROTA-S 400/500 THW 500-R/F ROTA THWB 400/500 THW 630-R
F 630 F+ 630		Duro 630 Duro-NC 630	ROTA-S plus 630/800/1000 ROTA-S 630/800/1000 ROTA-G 630



SMW-AUTOBLOK
96, 188




SMW-AUTOBLOK
156



SMW-AUTOBLOK
76

WAKS



Weiche Aufsatzbacken
breite Ausführung, für Backenschnellwechsel

- Kreuzversatz
- Werkstoff: 16MnCr5


Typ	Id.-Nr.	B	H ₁	H ₂	L	N	S	a	b	kg / Satz	SMW-AUTOBLOK
WAKS 140-10	012496	35	40	36	63	8	18	26	32	1.62	KNCS-N 140
WAKS 160-10	080931	25	50	46	85	8	18	42	32	1.94	HG-N 160
WAKS 160-20	080932	30	55.5	51.5	85			48	32	2.69	HG-F 160
WAKS 160-30	080933	40	80	76	70			26	32	4.43	KNCS-N 170 KNCS-2G 170
WAKS 200-10	080934	30	55.5	51.5	100	10	20	57	40	3.21	HG-N 210
WAKS 200-20	080935	30	70	66	100			45	40	4.09	HG-F 210
WAKS 200-30	012497	40	40	36	70			27	40	2.11	KNCS-N 210
WAKS 200-31	080936	40	60	56	85			42	40	4.02	KNCS-N 225
WAKS 200-32	036733	40	80	76	95			52	40	6.19	KNCS-NB 210 KNCS-NB 225 KNCS-2G 210 KNCS-2G 225
WAKS 250-10	080937	40	60	55	125	12	20	70	40	5.70	HG-N 260
WAKS 250-11	080938	40	80	75	125			70	40	7.71	HG-N 315
WAKS 250-12	080939	40	100	95	125			70	40	9.75	HG-F 260
WAKS 250-13	080940	40	120	115	125			70	40	11.80	KNCS-N 260/275
WAKS 250-20	012498	60	60	55	90			44	40	6.30	KNCS-N 325/340
WAKS 250-21	080942	60	60	55	110			60	40	7.78	KNCS-NB 260
WAKS 250-22	080943	60	80	75	90			44	40	8.50	KNCS-NB 325
WAKS 250-23	080944	60	80	75	110			60	40	10.58	KNCS-NB 340
WAKS 250-30	012499	80	60	55	90			44	40	8.68	KNCS-2G 260
WAKS 250-31	080945	80	80	75	110			60	40	14.48	KNCS-2G 325
WAKS 400-10	080946	40	60	54	110	12	26	54	54	4.88	HG-N 400
WAKS 400-11	080947	40	60	54	145			89	54	6.60	HG-2G 400
WAKS 400-12	080948	40	100	94	145			89	54	11.44	HG-F 315
WAKS 400-13	080949	40	120	114	145			89	54	13.86	KNCS-N 400
WAKS 400-14	080950	40	150	144	145			89	54	17.49	KNCS-NB 400
WAKS 400-20	080951	60	60	54	110			54	54	7.73	KNCS-2G 400
WAKS 400-21	080952	60	80	74	110			54	54	10.52	
WAKS 400-22	080953	60	100	94	110			54	54	13.32	
WAKS 400-30	012500	80	70	64	100			44	54	11.38	
WAKS 500-10	080954	60	80	73	155	18	30	90	60	14.17	HG-N 500
WAKS 500-12	080956	60	120	113	155			90	60	21.91	HG-N 630
WAKS 500-20	080957	80	80	73	155			90	60	19.70	HG-2G 500
WAKS 500-21	080958	80	100	93	155			90	60	25.04	HG-2G 630
WAKS 500-30	012501	90	80	73	130			65	60	18.50	HG-F 400/500
WAKS 500-31	012502	100	80	73	150			85	60	24.28	KNCS-N 500 KNCS-N 630 KNCS-NB 500 KNCS-NB 630 KNCS-NB 800 KNCS-2G 500 KNCS-2G 630

WAKS 200-10	080934-2*	30			100		57	2.10	KNCS-N 210
WAKS 200-20	080935-2*	30			100		45	2.70	
WAKS 200-30	012497-2*	40			70		27	1.40	
WAKS 200-31	080936-2*	40			85		43	2.70	
WAKS 200-32	036733-2*	40			95		52	4.10	
WAKS 250-10	080937-2*	40			125		70	3.80	KNCS-N 260 KNCS-N325
WAKS 250-11	080938-2*	40			125		70	5.10	
WAKS 250-12	080939-2*	40			125		70	6.50	
WAKS 250-13	080940-2*	40			125		70	7.90	
WAKS 250-20	012498-2*	60			90		44	4.20	
WAKS 250-21	080942-2*	60			110		60	3.20	
WAKS 250-22	080943-2*	60			90		44	5.70	
WAKS 250-23	080944-2*	60			110		60	7.00	
WAKS 250-30	012499-2*	80			90		44	5.80	
WAKS 250-31	080945-2*	80			110		60	9.70	

* Für 2-Backenfutter



- SMW-AUTOBLOK
- 96, 188



- SMW-AUTOBLOK
- 156



- SMW-AUTOBLOK
- 76

[illegible]