


GSG-D



Harte Stangengreifbacken


- Spitzverzahnung Zoll 1/16" x 90° oder 3/32" x 90°
- Spitzverzahnung geschliffen

| Typ                    | Id.-Nr. | Spann-<br>bereich Ø | B  | H  | N    | Spitz-<br>verzahnung | b für<br>ISO 4762 | kg /<br>Satz |
|------------------------|---------|---------------------|----|----|------|----------------------|-------------------|--------------|
| GSG-D 165 <sup>1</sup> | 091343  | 15-40               | 30 | 40 | 14   | 1/16" x 90°          | 20<br>M10         | 1.06         |
| GSG-D 200 <sup>2</sup> | 091344  | 15-50               | 35 | 45 | 17   | 1/16" x 90°          | 22<br>M12         | 1.50         |
| GSG-D 250 <sup>3</sup> | 091345  | 20-70               | 45 | 50 | 21   | 1/16" x 90°          | 28<br>M16         | 2.69         |
| GSG-D 400 <sup>4</sup> | 091346  | 40-100              | 55 | 60 | 25.5 | 3/32" x 90°          | 35<br>M20         | 7.78         |

- \* nur mit Einzelnutenstein  
<sup>1</sup> Spannungsbereich gültig für Futter Ø 165  
<sup>2</sup> Spannungsbereich gültig für Futter Ø 210  
<sup>3</sup> Spannungsbereich gültig für Futter Ø 260  
<sup>4</sup> Spannungsbereich gültig für Futter Ø 400

| SMW-AUTOBLOK                                                                                                                                                                                                                                                                      | Forkardt                                                                                                                                                                                                       | Röhm                                                                                                                                                                 | Schunk                                                                                                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| HFKN-D 165<br>SP/STP 160<br>AN/AL/BH/HB-D 165<br>BHD-FC 165<br>PB/PB/RC-D 165<br>AP/NT-D 170<br>BB-D 175<br>HYND-S 180<br>HFKN-D 210<br>SP/STP 200/240<br>AN/AL/BH/BB-D 210<br>BHD-FC 210<br>CC 240Z<br>HB/PB/PB/RC-D 210<br>AP/APL/NT-D 215<br>AP/APL/NT-D 260<br>HYND-S 210/226 |                                                                                                                                                                                                                |                                                                                                                                                                      | TP 160                                                                                                                                       |
| HFKN-D 260/315<br>SP/STP 280<br>SP/SP-L 350<br>AN/AL/BH/BB-D 250<br>AN/AL/BH/BB-D 315<br>BHD-FC 250/315<br>RC-D 250/305/400<br>CC 350Z<br>HB/PB/PB/RC-D 250/315<br>AP/APL/NT-D 315<br>HYND-S 250/315/400                                                                          | QLK/QLC 200<br>QLK/QLC-KS/LS 200<br>QLC-AG 200<br>NH/NHF 200<br>KL/KT/KTG/KTN/KS-PS 200<br>KS 200/250<br>KSF 200<br>KGH/KGHF/KTH 200<br>KG/KP 200<br>UVE 200                                                   | KFD/KFD-HF 200<br>KFH/KFH-F/KFH-G/KFH-NC 200<br>KFD-AF 200<br>KFD-HE 210<br>SPD/SPO 215<br>LVE 200                                                                   | TH/THF/HSL 210<br>ROTA NCD 210<br>ROTA NC/ROTA NCF/ROTA NCO 210<br>ROTA NCK plus 210/250<br>ROTA TP 200<br>TP 200                            |
| HFKN-D 400/500<br>AP/AP-L/NT-D 400*<br>BB-N 400/470/500/600<br>BB-N ES 400/470/500/600<br>BB-EXL(SC)2G 510/660<br>AN/AL/BB-D 400<br>BH-D 400/450/500/630/800<br>BHD-FC 400/500/630<br>IN/IL-D 500/630/800<br>HYDL-S 500/630/800                                                   | QLK/QLC 250/315<br>QLK/QLC-KS 315/400<br>QLK/QLC-LS 250/315<br>QLC-AG 250/315<br>KG/KT/KP/KTG/KTN/KTGF 250/315<br>KLNC/NH/NHF 250/315<br>KS 315/400<br>KSPS 250/300<br>KSH/KSHF 250/315/400<br>HF315<br>UVE315 | KFD/KFD-HF 250/315<br>KFH/KFH-F/KFH-G/KFH-NC 250/315<br>KFD-AF 250/315<br>KFD-HE 254/315<br>KFL 315/400<br>SPD/SPO 300<br>LVE 250/305/315                            | TH/THF/HSL 250/315<br>ROTA NC/ROTA NCD 250/315<br>ROTA NCF 250/315<br>ROTA NCO 260/315<br>ROTA NCK plus 315<br>ROTA TP 250/315<br>TP 250/315 |
|                                                                                                                                                                                                                                                                                   | QLK/QLC 400<br>NH/NHF 400/500/630<br>KT/KTGF 400/500/630<br>KS 500/630<br>KG/KL/KP/KLNC 400/500<br>KSHF 630<br>KSH 500<br>KSL 630<br>KSPS 400<br>UVE 400/500/630/800                                           | KFD 400/500/630/800<br>KFD-HF 400/500/630<br>KFD-HS 400/500<br>KFD-HE 400<br>KFH/KFH-F/KFH-G/KFH-NC 400/500<br>KFL 500/600<br>KFD-HE 400<br>LVE 400/500/630/800/1000 | TH/THF 400/500<br>HSL 400<br>HSG 400/500<br>ROTA NC/ROTA NCD 400/500<br>ROTA NCF/ROTA NCO 400/500                                            |

GFB-D



Harte Aufsatzbacken  
für GF-80


- Spitzverzahnung Zoll 1/16" x 90°
- Spitzverzahnung geschliffen

| Typ     | Id.-Nr. | Spann-<br>bereich Ø | B  | H  | N  | Spitz-<br>verzahnung | b für<br>ISO 4762 | kg /<br>Satz |
|---------|---------|---------------------|----|----|----|----------------------|-------------------|--------------|
| GFB-D 1 | 016348  | 5-25                | 25 | 39 | 10 | 1/16" x 90°          | M8                | 0.64         |
| GFB-D 2 | 016349  | 25-45               | 30 | 39 | 10 | 1/16" x 90°          | M8                | 0.62         |
| GFB-D 3 | 016350  | 45-65               | 30 | 39 | 10 | 1/16" x 90°          | M8                | 0.53         |
| GFB-D 4 | 016351  | 65-80               | 30 | 39 | 10 | 1/16" x 90°          | M8                | 0.47         |
| GFB-D 5 | 016352  | 80-100              | 30 | 39 | 10 | 1/16" x 90°          | M8                | 0.51         |

| SMW-AUTOBLOK | Forkardt | Röhm  | Schunk |
|--------------|----------|-------|--------|
| GF 80        |          | GF 80 |        |
| GF 80        |          | GF 80 |        |
| GF 80        |          | GF 80 |        |
| GF 80        |          | GF 80 |        |
| GF 80        |          | GF 80 |        |



SMW-AUTOBLOK  
188, 190



SMW-AUTOBLOK  
65