


MHB-D

Hard, reversible top jaws



- Inch serration 1/16" x 90° or 3/32" x 90°
- Serration ground




For highest accuracy we recommend to grind the jaws on the chuck under clamping conditions.

Type	Id. No.	B	H	L	T	N	Serration	a + b + c for ISO 4762	kg / Set	Number of jaws
MHB-D 110	007076	20	31	48.2	7	8	1/16" x 90°	14.5 + 12 + 12 M6	0.35	3
MHB-D 130	12081306	29.7	34	58.1	8.5	12	1/16" x 90°	13 + 16 + 16 M8	0.60	3
MHB-D 160	12081636	34	39	65.2	10	14	1/16" x 90°	18 + 16.5 + 16.5 M10	0.89	3
MHB-D 160	12081638**	34	39	65.2	10	14	1/16" x 90°	18 + 16.5 + 16.5 M10	0.90	4
MHB-D 200	12082036	40	45	82.7	10.5	17	1/16" x 90°	19 + 23 + 23 M12	1.68	3
MHB-D 200	12082038**	40	45	82	10.5	17	1/16" x 90°	19 + 23 + 23 M12	2.30	4
MHB-D 260	12082626	45	56	101.1	13.5	17	1/16" x 90°	23 + 30 + 30 M12	3.08	3
MHB-D 251	12083038**	45	56	106.2	13.5	21	1/16" x 90°	26 + 30 + 30 M16	2.90	4
MHB-D 251	12083036	45	56	106.2	13.5	21	1/16" x 90°	26 + 30 + 30 M16	2.87	3
MHB-D 315	12083186	45	56	123.6	13.5	21	1/16" x 90°	43 + 30 + 30 M16	3.72	3
MHB-D 401	12084506	60	75	141.1	19	21	1/16" x 90°	38 + 38 + 38 M16	5.10	3
MHB-D 500	12084546	60	75	140.8	19	25.5	3/32" x 90°	38 + 38 + 38 M20	7.10	3
MHB-D 500	12084548**	60	75	140.8	19	25.5	3/32" x 90°	38 + 38 + 38 M20	9.50	4
MHB-D 610 ¹	12086346	74	74	146.8	32	25.5	3/32" x 90°	46 + 38 + 38 M20	9.61	3

SMW-AUTOBLOK	Forkardt	Röhm	Schunk
HFKN-D 110			
AN/AL-D 125 BH/HB/PB-D 130 BB-D 140 SP/STP 125	KTH 130/140	KFD 130 KFH 140 KFD-HS 160/175 KFD-HE 170 LVE 125/160	HSG 160 ROTA NCD 165
HFKN-D 165 SP/STP 160 AN/AL/BH/HB-D 165 BHD-FC 165 PB/PBI/RC-D 165 AP/NT-D 170 BB-D 175 HYND-S 180 HFKS-2G-D 165 Centco4-D 210			
HFKN-D 210 SP/STP 200/240 AN/AL/BH/BB-D 210 BHD-FC 210 CC 240Z HB/PB/PBI/RC-D 210 AP/APL/NT-D 215 AP/APL/NT-D 260* HYND-S 210/226 HFKS-2G-D 210/255	QLK/QLC 160/175/200 QLK/QLC-KS 200/250 QLK/QLC-LS 160/200 QLC-AG 200 NH/NHF 160/175/200 KL/KT/KTG/KTN/KS-PS 160/200 KS 160/200/250 KSF 175/200 KGF/KGHF/KTH 160/175/200 KG/KP 200 UVE 160/200/250	KFD/KFD-HF 160/200 KFH/KFH-F/KFH-G/KFH-NC 160/200 KFD-AF 160/200 KFD-HE 210 SPD/SPO 160/215 LVE 200	TH/THF/HSL 165/210 ROTA NCD 185/210 ROTA NC/ROTA NCF 165/210 ROTA NCO 165/210 ROTA NCK plus 210/250 ROTA 2B 160 ROTA TP 200 TP 200
Centco4-D 260/315			
AP/APL/NT-D 260			
Centco4-D 400			
HFKN-D 260/315 SP/STP 280 HFKS-2G-D 320 SP/SP-L 350 AN/AL/BH/BB-D 250 AN/AL/BH/BB-D 315 BHD-FC 250/315 RC-D 250/305/400 CC 350Z HB/PB/PBI-D 250/315 AP/APL/NT-D 315 HYND-S 250/315/400 RC-D 400	QLK/QLC 250/315 QLK/QLC-KS 315/400 QLK/QLC-LS 250/315 QLC-AG 250/315 KG/KT/KP/KTG/KTN/KTGF 250/315 KLNC/NH/NHF 250/315 KS 315/400 KSPS 250/300 KSH/KSHF 250/315/400 HF315 UVE315	KFD/KFD-HF 250/315 KFH/KFH-F/KFH-G/KFH-NC 250/315 KFD-AF 250/315 KFD-HE 254/315 KFL 315/400 SPD/SPO 300 LVE 250/305/315	TH/THF/HSL 250/315 ROTA NC/ROTA NCD 250/315 ROTA NCF 250/315 ROTA NCO 260/315 ROTA NCK plus 315 ROTA TP 250/315 TP 250/315
HFKN-D 400/500 AP/AP-L/NT-D 400* BB-N 400/470/500/600 BB-N ES 400/470/500/600 BB-EXL(SC)2G 510/660 AN/AL/BB-D 400 BH-D 400/450/500/630/800 BHD-FC 400/500/630 IN/IL-D 500/630/800 HYDL-S 500/630/800 Centco4-D 500/630	QLK/QLC 400 NH/NHF 400/500/630 KT/KTGF 400/500/630 KS 500/630 KG/KL/KP/KLNC 400/500 KSHF 630 KSH 500 KSL 630 KSPS 400 UVE 400/500/630/800	KFD 400/500/630/800 KFD-HF 400/500/630 KFD-HS 400/500 KFD-HE 400 KFH/KFH-F/KFH-G/KFH-NC 400/500 KFL 500/600 KFD-HE 400 LVE 400/500/630/800/1000	TH/THF 400/500 HSL 400 HSG 400/500 ROTA NC/ROTA NCD 400/500 ROTA NCF/ROTA NCO 400/500
BH-D 630/800 IN/IL-D 630/800 HYDL-S 500/630/800	NH/NHF 630 KT/KTGF 630 KS 630 KSHF 630 KSL 630 UVE 630/800	KFD 630/800 LVE 630/800/1000	

¹ 1 step only
* With single T-nuts only
** 1 Set = 4 pieces



SMW-AUTOBLOK
188, 190

SMW-AUTOBLOK
65