



NSTE

Double T-nuts



Version 1

- Quenched and ground
- Incl. screw ISO 4762 – 12.9



Version 2



Please observe!
Always tighten T-nuts
with a torque wrench.

| Type | Id. No. | Version | N | H | h | b | G | Screw ISO 4762 | Torque Md max. (Nm) | SMW-AUTOBLOK |
|-------------|----------|---------|------|------|------|------|-----|-------------------|------------------------|---|
| NSTE 08 | 038265 | 2 | 8 | 13.5 | 5 | 12 | M6 | M6 x 20 | 16 | HFKN-D 110 |
| NSTE 12 | 12061300 | 2 | 12 | 15 | 6.5 | 16 | M8 | M8 x 20 | 30 | BH-D 130 PB-D 130 HB-D 130 BB-D 140 |
| NSTE 12-1 | 12061200 | 1 | 12 | 15 | 5.5 | 16 | M8 | M8 x 20 | 30 | AN-D 125 AL-D 125 |
| NSTE 14 | 73061650 | 1 | 14 | 18.5 | 6.5 | 16.4 | M10 | M10 x 20 | 50 | HFKN-D 165 AN/AL/BH/BH-D 165 BHD-FC 165 PB/PBI/RC-D 165 AP/NT-D 170 BB-D 175 HYND-S 180 |
| NSTE 17 | 081813 | 2 | 17 | 23 | 9 | 22 | M12 | M12 x 30 | 70 | |
| NSTE 17-1 | 081814 | 2 | 17 | 23 | 9 | 19 | M12 | M12 x 30 | | |
| NSTE 17-2 | 73062150 | 1 | 17 | 20.5 | 7.5 | 23 | M12 | M12 x 25 | 70 | HFKN-D 210 • AN-D 210 AL-D 210 • BH-D 210 BHD-FC 210 • RC-D 210 BB-D 210 • PB-D 210 PBI-D 210 • HB-D 210 HYDN-S 210/226 AP-D 215 • NT-D 215 |
| NSTE 17-3 | 18062632 | 1 | 17 | 20.5 | 7 | 30 | M12 | M12 x 25 | 70 | AP-D 260 NT-D 260 |
| NSTE 21 | 081815 | 2 | 21 | 27 | 11 | 28 | M16 | M16 x 35 | 150 | |
| NSTE 21-2 | 73063050 | 1 | 21 | 26.5 | 10 | 30 | M16 | M16 x 30 | 150 | HFKN-D 260/315 • HFKN-M 315 AN/AL/BH/BB/BB/PB/PBI-D 250/315 |
| NSTE 21-3 | 034148 | 1 | 21 | 26.5 | 10 | 28 | M16 | M16 x 30 | 150 | AN/AL/BH/BB/PB/PBI-M 315 AP/APL/NT-D 315 AP/APL/NT-M 315 HYND-S 250/315 • RC-D 250/305 RC-M 305 • BHD-FC 250/315 BHM-FC 315 |
| NSTE 25.5 | 081817 | 2 | 25.5 | 29 | 11 | 35 | M20 | M20 x 40 | 300 | HFKN-D 400 HFKN-M 400 |
| NSTE 25.5-1 | 73065030 | 1 | 25.5 | 33 | 14.5 | 38 | M20 | M20 x 40 | 300 | RC-D 500 AP-D 400 • APL-D 400 NT-D 400 |

| Forkardt | Schunk |
|---|---|
| | |
| | |
| | |
| | |
| | |
| 2 BLE-PS 160/200 • 2 BLEF 200 KL/KT/KTG/KTN/KS-PS 160/200 KSF 175/200 • KSKL 250 Mo KGH/KGHF/KTH 160/175/200 KS 160/200/250 • KG/KP 200 NH/NHF 160/175/200 QLK/QLC 160/175/200 QLK/QLC-KS 200/250 QLK/QLC-LS 160/200 QLC-AG 200 • UVE 160/200/250 | HSL 165/210 TH 165/210 THF 165/210 ROTA NC-D 200 HSG 200 HSG 250 ROTA NC/NCF Plus 165 |
| | ROTA NC/NCF Plus 215 ROTA NCO 210 ROTA NCD 185 ROTA NCK Plus 210/250 ROTA NCF 165/210 ROTA NC 165/210 ROTA 2B 160 |
| | |
| 3 NH 250-315 • 3 NHF 250-315 KT 250-315 • KSH 250-315 KSHF 250-315 • 3 KTGF 250-315 KG 250-315 • KP 250-315 KLNC 250-315 • KL 250 • KSPS 250-300 3 NHF 290 • KS 315-400 • KSH 400 KSHF 400 • UVE 315 • 3 NHD 400 (Index) 2 BLE 200 • 2 BLE 250 Mo QLK/QLC 250/315 • QLK/QLC-KS 315/400 QLK/QLC-LS 250/315 • QLC-AG 250/315 | HSL 250/315 ROTA NC-D 250 ROTA NC-O 250 TH 250/315 THF 250/315 HSG 315 ROTA NC-D 315 ROTA NC-O 315 ROTA NCF 315 ROTA NC 315 ROTA NCO 260/315 ROTA 2B 200 ROTA NC 250 • ROTA NCF 250 ROTA NC Plus 260/315 ROTA NCK Plus 315 ROTA NCF Plus 260/315 |
| | |
| 3 NH 400-500-630 • 3 NHF 400-500-630 3 KTGF 400-500 • UVE 400-500-630-800 KT 400-500 • KG 400-500 • KL 400-500 KLNC 400-500 • KP 400 • KS 500-630 KSH 500 • KSL 630 • KSHF 630 • KL 300 KSHF 560 • 2 BLE 250 • 2 BLE 315 2 BLE-PS 300 • 2 BLE-PS 315 • 2 BLE 400 2 BLE 500 • 2 BLE-PS 400-500 • QLC 400 • QLK 400 | HSL 400 ROTA NC-D 400/500 ROTA NC-F 400/500 TH 400/500 THF 400/500 ROTA 2B 250/315/400 |