


WAKA




Soft top jaws 2, 3 and 4 jaw versions for power chucks

- American Standard tongue and groove
- Material: C45

| Type | Id. No. | B | H ₂ | L | N | D | E | I | ISO 4762 | kg / piece | SMW-AUTOBLOK |
|-----------|----------|----|----------------|-----|------|----|------|-------|----------|------------|---|
| WAKA 165* | 12041660 | 30 | 32 | 80 | 7.94 | 30 | 38 | 12.68 | M10 | 0.47 | RAN 160 AN-C 165 HB-C 165 PB-C 165 PBI-C 165 AP-C 170 NT-C 170 RAN 200 |
| WAKA 210* | 12042060 | 35 | 37 | 100 | 7.94 | 35 | 44.4 | 12.68 | M12 | 0.81 | AN-C 210 HB-C 210 PB-C 210 PBI-C 210 AP-C 215 APL-C 215 NT-C 215 RAN 250 |
| WAKA 250* | 12042560 | 45 | 42 | 120 | 12.7 | 42 | 54 | 19.03 | M16 | 1.40 | AN-C 250 HB-C 250 PB-C 250 PBI-C 250 RAN 250 AP-C 260 APL-C 260 NT-C 260 |
| WAKA 315* | 12043060 | 50 | 47 | 140 | 12.7 | 50 | 63.5 | 19.03 | M16 | 2.14 | AN-C 315 HB-C 315 PB-C 315 PBI-C 315 RAN 315 AP-C 315 APL-C 315 NT-C 315 |
| WAKA 400 | 12044050 | 60 | 55 | 165 | 12.7 | 60 | 76.2 | 19.03 | M20 | 3.53 | AN-C 400 AP-C 400 APL-C 315 NT-C 400 RAN 400 |
| WAKA 500 | 12045050 | 75 | 70 | 165 | 12.7 | 60 | 76.2 | 19.03 | M20 | 5.83 | IL-C 500 IL-C 630 IL-C 800 IN-C 500 IN-C 630 IN-C 800 |

* Jaws pointed



SMW-AUTOBLOK
96, 188



SMW-AUTOBLOK
76