


MFG



Hard base jaws for quick jaw change

- Modular serration inclined System Forkardt
- Inclusive jaw mounting bolts ISO 4762 – 12.9

| Type | Id. No. | B | H | L | N | S | G x Length (tapped hole) | kg/ Set | SMW-AUTOBLOK |
|---------|---------|----|------|-----|----|----|-----------------------------|------------|----------------------|
| MFG 160 | 081303 | 20 | 29.5 | 74 | 18 | 8 | M8 x 1.0 x 16 | 0.68 | HG-F 160 |
| MFG 200 | 081304 | 22 | 35 | 90 | 20 | 10 | M8 x 1.0 x 16 | 1.14 | HG-F 210 |
| MFG 250 | 081305 | 26 | 40 | 110 | 20 | 12 | M12 x 1.5 x 20 | 1.82 | HG-F 260 |
| MFG 315 | 081306 | 32 | 46 | 125 | 26 | 12 | M12 x 1.5 x 25 | 2.90 | HG-F 315 |
| MFG 400 | 081307 | 45 | 55 | 160 | 30 | 18 | M16 x 1.5 x 30 | 6.43 | HG-F 400 HG-F 500 |
| MFG 630 | 034266 | 65 | 62 | 230 | 40 | 24 | M20 x 33 | 16.13 | HG-F 630 |

| Forkardt | Samchully | Kitagawa | Röhms | Schunk |
|---|-----------|---|--|---|
| F 160 F+160 KTNC 160 FNC 175 KTNCV 160/175 | | | Duro 160 Duro-NC 160 Duro-NC 175 Duro-NCE 160 | ROTA-S 160 ROTA-S PLUS 160 |
| F 200 F+200 KTNC 200 FNC 200 KTNCV 200 | | QJ 8" (QJ 210-43) | Duro 200 Duro-NC 200 Duro-NCE 200 Duro-NC 225 | ROTA-S 200 THW 210 F ROTA-S PLUS 200 ROTA NC-WF 210 |
| F 250 F+250 UNC 250/315 FNC 250/315 KTNC 250/280/315 KTNCV 250/315 | | QJ 10/12" (QJ 254-65) (QJ 315-78) | Duro 250 Duro-NC 250 Duro-NCE 250/315 | ROTA-S 250 THW 250 F THW 265 F ROTA NC-WF 250 ROTA NC-WF 315 ROTA-S PLUS 250 |
| F 315 F+315 UNC 400 FNC 400 KTNC 360/400 KTNCV 400 | | | Duro 315 Duro-NC 315 Duro-NCE 400 | ROTA-S 315 THW 315 F THW 400 F ROTA-S PLUS 315 |
| F 400/500-L F+400/500 UNC 500 KTNC 500/630 FNC 500/630 KTNCV 500/630 | | | Duro 400/500 Duro-NC 400/500 Duro-NCE 500 | ROTA-S 400 ROTA-S 500 THW 500 F ROTA-S PLUS 400 ROTA-S PLUS 500 |
| F 630 F+630 | | | Duro 630 Duro-NC 630 | ROTA-S 630 ROTA-S plus 630 |