

NT-RC

Quick jaw change
TONGUE & GROOVE


NT-RD

Quick jaw change
SERRATION

Quick jaw change high precision power chuck

Ø 170 - 400 mm

- Centrifugal force compensation
- 3 jaws, closed center
- proofline® chucks = fully sealed – low maintenance



Application/customer benefits

- For mid to large batches flexible production / high speed machining and for fragile parts
- Quick jaw change = short set up time
- Fully sealed, ideal for dry machining of castings and forgings or if high pressure coolant is used
- Ideal for vertical, pick up and horizontal machines

NT-RC: Quick jaw change with TONGUE & GROOVE master jaws

NT-RD: Quick jaw change with serrated master jaws (2.5 mm x 60°)
(radially adjustable)

Technical features

- High accuracy patented quick jaw change
- Centrifugal force compensation
- Constant gripping force with permanent grease lubrication
- Central bore for coolant and / or air
- Chuck body and internal parts case hardened
- **proofline® chucks** = fully sealed – low maintenance



Standard equipment

3-jaw chuck
1 set soft top jaws
1 quick jaw change wrench
Mounting bolts

Ordering example

3-jaw chuck NT-RC 215 / A6
or
3-jaw chuck NT-RD 260 / Z220

Actual gripping force diagrams



The data in the diagrams refer to 3-jaw chucks, newly maintained according to their service manuals using SMW-AUTOBLOK K67 grease. The static and dynamic gripping forces have been measured using standard soft top jaws, placed in a position not exceeding the outer diameter of the chuck.

△ Safety advice / danger of damage:

When using taller / heavier jaws and / or clamping on a bigger diameter reduce draw pull / rotating speed accordingly.


Technical data

SMW-AUTOBLOK Type		NT-RD 170 NT-RC 170	NT-RD 215 NT-RC 215	NT-RD 260 NT-RC 260	NT-RD 315 NT-RC 315	NT-RD 400 NT-RC 400
Number of jaws		3	3	3	3	3
Radial jaw stroke	mm	3.6	4.6	5	6.3	7
Axial piston stroke	mm	17	22	24	30	33
Max. draw-pull*	kN	30	42	55	65	75
Max. gripping force*	kN	72	112	150	180	210
Max. speed	r.p.m.	6500	6000	4800	4000	3200
Weight (without top jaws)	kg	13	25	40	68	112
Moment of inertia	kg·m ²	0.048	0.146	0.34	0.84	2.15
Recommended actuating cylinders		SIN-S 100	SIN-S 100 / 125	SIN-S 125 / 150	SIN-S 125 / 150	SIN-S 150 / 175
Id.-No. NT-RC (Center mounting)		77188317	77188321	77188326	77188331	77188340
Id.-No. NT-RD (Center mounting)		77183317	77183321	77183326	77183331	77183340

* For internal clamping reduce the draw pull by 30%.



SMW-AUTOBLOK
466



SMW-AUTOBLOK
172



SMW-AUTOBLOK
327

Quick jaw change high precision power chuck

Ø 170 - 400 mm

■ Centrifugal force compensation

■ 3 jaws, closed center


■ proofline® chucks = fully sealed – low maintenance

NT-RC

Quick jaw change
TONGUE & GROOVE

NT-RD

Quick jaw change
SERRATION



Subject to technical changes.

For more detailed information please ask our customer service.

SMW-AUTOBLOK Type			NT-RD 170 NT-RC 170		NT-RD 215 NT-RC 215		NT-RD 260 NT-RC 260			NT-RD 315 NT-RC 315		NT-RD 400 NT-RC 400	
Mounting			Z140	A5	Z170	A6	Z220	A6	A8	Z220	A8	Z300	A11
	A	mm	172		216		262			315		390	
	BF/BA H6	mm	140	82.563	170	106.375	220	106.375	139.719	220	139.719	300	196.869
	C	mm	104.8		133.4		171.4	-	171.4	171.4		235	
	CA	mm	-	-	-	-	-	133.4	-	-	-	-	-
	D	mm	11.5		13.5		17	13.5	17	17		21	
	E	mm	32		42			48		48		75	
	F2	mm	M24 x 2		M32 x 1.5			M38 x 1.5		M38 x 1.5		M60 x 1.5	
	G H8	mm	25		33			39		39		61	
	HF/HA	mm	92	102	104	116	118	137	132	125	139	149	164
	K	mm	18.5		20			25		25		48	
	L	mm	43		52			58		58		74	
	M	mm	M10 x 1		M22 x 1.5			M28 x 1.5		M28 x 1.5		M52 x 1.5	
	N H9	mm	15		24			34		34		60	
	Q	mm	4.5		5.5			5.5		5.5		9	
Max.	R	mm	56		72			88		105		133.5	
Chuck open	R1	mm	86.5		108			131		157.5		195	
	R2 *	mm	99		122.5			145.5		172		217.5	
Max. / min.	S	mm	20 / 3		19 / -3			22 / -2		20 / -10		33 / 0	
Chuck fully closed	T	mm	175		220			-		-		-	
Radial jaw stroke	U	mm	3.6		4.6			5		6.3		7	
	W	mm	22		26			26		26		38	
	YF/YA	mm	5	15	5	17	5	24	19	5	19	6	21
Max. / min.	Z	mm	17 / 0		22 / 0			24 / 0		30 / 0		33 / 0	
	a	mm	3		3			3		3		3	
Min.	b	mm	8.5		12			14		16.5		31	
Min.	c	mm	9		13			14		16		38	
	d	mm	2.5 x 60°		2.5 x 60°			2.5 x 60°		2.5 x 60°		2.5 x 60°	
	e	mm	68		85			106		128.5		150	
	f	mm	5		5			5		5		7	
	g	mm	7.5		7.5			8.5		9.5		11.5	
	g1	mm	8		8			9		10		12	
	g2	mm	3.5		3.5			3.5		3.5		5.5	
	j	mm	30		38			44		54		63	
	l1	mm	2.5		2.5			9		9		8.5	
	l2	mm	52		66			78		95		118	
	n h8	mm	10		10			12		14		18	
	n1	mm	16		16			19		22		28	
	o H7	mm	12.68		12.68			19.03		19.03		19.03	
	p1	mm	16		16			21		21		37.5	
	p2	mm	-		-			-		60		80	
	p3	mm	38		49			55		62.5		83	
	p4	mm	-		80			70		80		110	
	p5	mm	65		80			102		102		140	
	p6	mm	70		-			102		120		155	
	p7	mm	-		-			-		135		170	
	p8	mm	-		-			-		-		170	
	q1	mm	-		-			-		30		36	
	q2	mm	36		45			60		60		80	
	r1	mm	M5 / 7		M5 / 8			M6 / 10		M6 / 10		M6 / 12	
	r2	mm	M6 / 14		M8 / 17			M8 / 17		M8 / 17		M10 / 19	
	r3	mm	M8 / 17		M8 / 17			M10 / 19		M10 / 19		M12 / 22	
	s	mm	16		16			16		16		20	
	t	mm	5		5			5		5		5	

* Quick jaw change position.

AP-R


Quick jaw change

NT-R

Quick jaw change

Quick change soft and hard top jaws


- Only for AP-RD, AP-RC, NT-RD, NT-RC
- Soft and hard jaws for chucks with serration (2.5 mm x 60°)
- Soft jaws for chucks with tongue & groove
- Torque wrench for quick jaw change

MHB-D**Hard top jaws with 2.5 x 60° serration for AP-RD and NT-RD chucks**


First operation jaws, if high concentricity is required jaws have to be ground on chuck.

Chuck Ø	Id. No.*	Serration mm	B mm	H mm	L mm	N mm	T mm	a mm	b mm	c mm	Weight kg / each
170	18081736	2.5 x 60°	30	45	65	10	10	23	24	18	0.36
215	18082136	2.5 x 60°	35	46	82	10	10.5	24	36	22	0.57
260	18082636	2.5 x 60°	45	56	100	12	14.5	27	39	34	1.04
315	18083136	2.5 x 60°	45	57	105	14	14	27	42	36	1.09
400	18084036	2.5 x 60°	55	73	140	18	18.5	42	49	49	2.27


* the number refers to a set of 3 jaws

WBSA-D**Soft top jaws with 2.5 x 60° serration for AP-RD and NT-RD chucks**


Chuck Ø	Id. No.	Serration mm	B mm	H mm	L mm	N mm	Weight kg / each
170	18071730	2.5 x 60°	30	40	70	10	0.48
215	18072130	2.5 x 60°	35	45	90	10	0.87
260	18072630	2.5 x 60°	45	60	100	12	1.70
315	18073130	2.5 x 60°	45	60	120	14	2.05
400	18074030	2.5 x 60°	55	75	140	18	3.87

WAK-A**Soft top jaws with tongue & groove "C" for AP-RC and NT-RC chucks**

Chuck Ø	Id. No.	B mm	H mm	L mm	N mm	D mm	I mm	Weight kg / each
170	18041730	30	37	80	10	30	12.70	0.52
215	18042130	35	44	100	10	35	12.70	0.97
260	18042630	45	57	120	12	42	19.03	2.02
315	18043130	45	57	140	14	50	19.03	2.30
400	18044030	55	70	165	18	60	19.03	4.20

Gripping ranges using standard hard top jaws on AP-RD and NT-RD chucks

Chuck Ø	Id. No.	A1 mm	A2 mm	A3 mm	A4 mm	J1 mm	J2 mm	J3 mm
170	18081736	15-75	-	55-115	105-155	65-120	110-170	145-205
215	18082136	20-95	-	65-145	140-200	75-150	140-215	185-260
260	18082636	20-105	-	95-175	170-245	80-160	150-235	220-305
315	18083136	35-130	-	105-205	190-290	110-195	190-280	265-350
400	18084036	45-170	-	145-275	245-370	135-255	230-350	325-450

Spare quick jaw change T-wrenches

- Normal T-wrenches
- Torque wrenches for correct tightening of the quick jaw change bolt (option)

Chuck Ø	Hexagon mm	Correct torque Md Nm	"T" wrench Id. No.
170	6	23	51500812
215	8	45	51500816
260	10	70	51500820
315	12	110	51500822
400	14	200	51500824

Special grease for fully sealed chucks

- Resistant against high surface pressure
- For long lubrication intervals
- For proofline® chucks

Grease Grease Gun

**Important for maintenance and safe operation,
to be ordered with the chuck**

Grease K67®

Special grease for fully sealed chucks
included in proofline® series



Cartridge 14 Oz. (DIN 1284)
Grease content 500 g
Id. No. 10731223

Can 1000 g
Id. No. 10731224



- For proofline chucks with permanent grease lubrication
- Basic components: mineral oils and lithium
- Without solvents

Grease gun

Grease gun (DIN 1283) for
cartridges 14 Oz. (DIN 1284)

- Also refillable from grease can 1000 g



Lubrication set Id. No. 083726

Supply range

- Grease gun
- 1 Adapter flexible for high pressure grease nipple
- 1 Adapter for cone grease nipple